



COMPLETE CARWASH SUPPLIES

12 ENTERPRISE CIRCUIT, PRESTONS NSW 2170

Phone: 1300 722 435

ABN 24 262 329 805

ACN 114 640 729

Email: sales@completecarwash.com.au

SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

| | |
|-----------------------------|--|
| Trade Name: | Silicone Tyre Gloss |
| Chemical nature: | Blend of silicones and liquid hydrocarbon. |
| Product Use: | Tyre gloss preparation. |
| Creation Date: | June, 2008 |
| This version issued: | July, 2024 and is valid for 5 years from this date. |

SECTION 2 - HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. T, Toxic. N, Dangerous to the environment. F+, Highly Flammable. Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: S5

ADG Classification: Class 3: Flammable liquids.

UN Number: 1993, FLAMMABLE LIQUID, N.O.S.



GHS Signal word: DANGER.

HAZARD STATEMENT:

- H225: Highly flammable liquid and vapour.
- AUH066: Repeated exposure may cause skin dryness or cracking.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H320: Causes eye irritation.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H411: Toxic to aquatic life with long lasting effects.

PREVENTION

- P102: Keep out of reach of children.
- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
- P233: Keep container tightly closed.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P262: Do not get in eyes, on skin, or on clothing.
- P264: Wash contacted areas thoroughly after handling.
- P271: Use only outdoors or in a well ventilated area.
- P273: Avoid release to the environment.
- P281: Use personal protective equipment as required.

RESPONSE

- P362: Take off contaminated clothing and wash before reuse.
- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+P352: IF ON SKIN or hair: Wash with plenty of soap and water.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SAFETY DATA SHEET

Issued by: Complete Carwash Supplies

Phone: 1300 722 435

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog.

STORAGE

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

DISPOSAL

P501: If product can not be recycled, consider controlled incineration, or contact a specialist waste disposal company (see Section 13 of this SDS).

Emergency Overview

Physical Description & colour: Clear, colourless liquid.

Odour: Characteristic hydrocarbon odour.

Major Health Hazards: irritating to eyes and skin, eye irritant, possible risk of impaired fertility, if aspirated, may cause lung damage, vapours may cause drowsiness and dizziness.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredients | CAS No | Conc,% | TWA (mg/m ³) | STEL (mg/m ³) |
|---------------------|---------|--------|--------------------------|---------------------------|
| Liquid hydrocarbon | no data | >85 | not set | not set |
| Silicone derivative | no data | to 100 | not set | not set |

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

SECTION 4 - FIRST AID MEASURES

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Gently blot away excess liquid. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

SECTION 5 - FIRE FIGHTING MEASURES

Fire and Explosion Hazards: This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Suitable extinguishing media are carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal foam can be used. Try to contain spills, minimise spillage entering drains or water courses.

SAFETY DATA SHEET

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: Below 0°C

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC, Viton. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

SECTION 7 - HANDLING AND STORAGE

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

Exposure limits have not been established by SWA for any of the significant ingredients in this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

SAFETY DATA SHEET

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC, Viton.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:

| | |
|---|-----------------------------------|
| Physical Description & colour: | Clear, colourless liquid. |
| Odour: | Characteristic hydrocarbon odour. |
| Boiling Point: | 70-135°C at 100kPa (solvent) |
| Freezing/Melting Point: | Below 0°C. |
| Volatiles: | Approx 75% |
| Vapour Pressure: | No data. |
| Vapour Density: | No data. |
| Specific Gravity: | 0.70 approx |
| Water Solubility: | Insoluble. |
| pH: | No data. |
| Volatility: | No data. |
| Odour Threshold: | No data. |
| Evaporation Rate: | No data. |
| Coeff Oil/water distribution: | No data. |
| Autoignition temp: | No data. |

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

Incompatibilities: oxidising agents.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water, silicon compounds, silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicity: A summary of white spirit type hydrocarbons can be found at <http://www.inchem.org/documents/ehc/ehc/ehc187.htm>

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea.

Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure.

Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few ml of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30ml may be fatal.

Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reportings, the relevance of these findings is unclear.

This product may cause decreased fertility. Overexposure to hexane (an ingredient in this product) may cause effects on the peripheral nerves, resulting in weakness or numbness of the lower limbs.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity but are CNS depressants and have a disinhibiting euphoric effect.

Potential Health Effects

Inhalation:

Short term exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term inhalation.

SAFETY DATA SHEET

Skin Contact:

Short term exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

SECTION 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. This product is not readily biodegradable. However, likely to degrade slowly in the soil or water.

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. This product should be suitable for landfill. However, check with local Waste Disposal Authority before sending there. Note that product properties may have been changed in use, significantly altering its suitability for landfill. Please do NOT dispose into sewers or waterways.

SECTION 14 - TRANSPORT INFORMATION

ADG Code: 1993, FLAMMABLE LIQUID, N.O.S.

Hazchem Code: 3YE

Special Provisions: 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

Dangerous Goods Class: Class 3: Flammable liquids.

Packaging Group: II

Packaging Method: P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

SECTION 15 - REGULATORY INFORMATION

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

SECTION 16 - OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

Acronyms:**SAFETY DATA SHEET**

| | |
|---------------------|---|
| ADG Code | Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition) |
| AICS | Australian Inventory of Chemical Substances |
| SWA | Safe Work Australia, formerly ASCC and NOHSC |
| CAS number | Chemical Abstracts Service Registry Number |
| Hazchem Code | Emergency action code of numbers and letters that provide information to emergency services especially firefighters |
| IARC | International Agency for Research on Cancer |
| NOS | Not otherwise specified |
| NTP | National Toxicology Program (USA) |
| R-Phrase | Risk Phrase |
| SUSMP | Standard for the Uniform Scheduling of Medicines & Poisons |
| UN Number | United Nations Number |

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared for Complete Carwash Supplies in accord with the SWA document "National Code of Practice for the Preparation of Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, July, 2024.

<http://www.kilford.com.au/> Phone (02)9251 4532

SAFETY DATA SHEET